

K4ICY Bite Sized Band Plans

US Amateur Radio (FCC Effective Date 03/05/12)

This page will make wallet cards for both HF and VHF/UHF band plans.

Compiled by Mike Maynard K4ICY at k4icy@arrl.net

Instructions:

Print same image on front & back of card weight paper to make a double sided wallet card.

Or print once and fold accordingly if using regular paper.

Resize as needed.

Cut or Fold

<p>US Amateur Radio Bite Sized Band Plans FCC Effective Date: 03/05/12</p> <h2>HF</h2> <p>160 Meters 1.800-2.000 EXTRA • ADVANCED • GENERAL CW/Phone/Image/Data 1.800-2.000</p> <p>MODES 1.800-2.000 CW 1.800-1.810 Digital Modes 1.810 CW QRP 1.843-2.000 SSB, SSV and other wideband modes</p> <p>PLANS 1.910 SSB QRP 1.995-2.000 Experimental 1.999-2.000 Beacons 1900-2000 Avoid QRM to radiolocation opt.</p> <p>80/75 Meters 3.500-4.000 EXTRA CW/RTTY/Data 3.500-3.800 Phone/CW/Image 3.600-4.000</p> <p>ADVANCED CW/RTTY/Data 3.525-3.800 Phone/CW/Image 3.700-4.000</p> <p>GENERAL CW/RTTY/Data 3.525-3.800 Phone/CW/Image 3.800-4.000</p> <p>TECHNICIAN • NOVICE CW (20W Max PEP) 3.525-3.800</p> <p>3.500-3.510 CW DX Window 3.560 QRP CW Calling Freq. 3.570-3.600 RTTY/Data 3.585-3.800 Auto Cent. Data Stations 3.590 RTTY/Data DX 3.790-3.800 DX Window 3.845 SSV 3.885 AM Calling Freq. 3.985 QRP SSB Calling Freq.</p>	<p>60 Meters Channelized EXTRA • ADVANCED • GENERAL Tuning Frequency Channel Center 5.330.50 5.332.00 5.346.50 5.348.00 5.357.00 5.358.50 5.371.50 5.373.00 5.403.50 5.405.00</p> <p>CHANNLES</p> <p>40 Meters 7.000-7.300 EXTRA CW/RTTY/Data 7.000-7.125 Phone/CW/Image 7.125-7.300</p> <p>ADVANCED CW/RTTY/Data 7.025-7.125 Phone/CW/Image 7.125-7.300</p> <p>GENERAL CW/RTTY/Data 7.025-7.125 Phone/CW/Image 7.175-7.300</p> <p>TECHNICIAN • NOVICE CW (20W Max PEP) 7.025-7.125</p> <p>7.030 QRP CW Calling Freq. 7.040 RTTY/Data DX 7.080-7.125 RTTY/Data 7.080.15 PSK31 7.100-7.105 Auto Cent. Data Stations 7.171 SSV 7.285 QRP SSB Calling Freq. 7.290 AM Calling Freq.</p> <p>30 Meters 10.100-10.150 EXTRA • ADVANCED • GENERAL CW & Data Only 10.100-10.150 (20W Max PEP)</p> <p>10.100 QRP CW Calling Freq. 10.130-10.140 RTTY/Data 10.140-10.150 Auto Cent. Data Stations</p> <p>PLANS Avoid QRM to fixed services outside the US. ©2012 Mike Maynard K4ICY • k4icy@arrl.net Free PDF - Visit k4icy.com</p>	<p>20 Meters 14.000-14.350 EXTRA CW/RTTY/Data 14.000-14.150 Phone/CW/Image 14.150-14.350</p> <p>ADVANCED CW/RTTY/Data 14.025-14.150 Phone/CW/Image 14.175-14.350</p> <p>GENERAL CW/RTTY/Data 14.025-14.150 Phone/CW/Image 14.225-14.350</p> <p>14.070.15 PSK31 14.100 IBP/NCDX Beacons 14.100.50-14.112 Auto Cent. Data Stations 14.230 SSV 14.285 QRP SSB Calling Freq. 14.286 AM Calling Freq.</p> <p>17 Meters 18.068-18.168 EXTRA • ADVANCED • GENERAL CW/RTTY/Data 18.068-18.110 Phone/CW/Image 18.110-18.168</p> <p>18.100-18.105 RTTY/Data 18.105-18.110 Auto Cent. Data Stations 18.110 IBP/NCDX Beacons</p> <p>15 Meters 21.000-21.450 EXTRA CW/RTTY/Data 21.000-21.200 Phone/CW/Image 21.200-21.450</p> <p>ADVANCED CW/RTTY/Data 21.025-21.200 Phone/CW/Image 21.225-21.450</p> <p>GENERAL CW/RTTY/Data 21.025-21.200 Phone/CW/Image 21.275-21.450</p> <p>TECHNICIAN • NOVICE CW (20W Max PEP) 21.025-21.200</p> <p>21.060 QRP CW Calling Freq. 21.070-21.110 RTTY/Data 21.090-21.100 Auto Cent. Data Stations 21.150 IBP/NCDX Beacons 21.340 SSV 21.385 QRP SSB Calling Freq.</p>	<p>12 Meters 24.890-24.990 EXTRA • ADVANCED • GENERAL CW/RTTY/Data 24.890-24.930 Phone/CW/Image 24.930-24.990</p> <p>24.920-24.925 RTTY/Data 24.925-24.930 Auto Cent. Data Stations 24.930 IBP/NCDX Beacons</p> <p>10 Meters 28.000-29.700 EXTRA • ADVANCED • GENERAL CW/RTTY/Data 28.000-28.300 Phone/CW/Image 28.300-29.700</p> <p>TECHNICIAN • NOVICE CW/RTTY/Data 28.000-28.300 Phone Only 28.300-28.500</p> <p>28.060 QRP CW Calling Freq. 28.070-28.120 RTTY/Data 28.100-28.150 Auto Cent. Data Stations 28.190-28.225 Beacons 28.200 IBP/NCDX Beacons 28.385 QRP SSB Calling Freq. 28.680 SSV 29.000-29.200 AM 29.300-29.510 Satellite Downlinks 29.520-29.580 Repeater Inputs 29.600 FM Simplex 29.600-29.700 FM 29.600-29.680 Repeater Outputs</p> <p>Band limits are to be followed according to the operator's license class privileges. Operators must stay within the band edges providing enough room for transmitting mode bandwidth. 1600 Watts PEP output is allowed to all non-Beacons unless otherwise noted. Please stay within FCC section 97 guidelines. The lower Band Plan descriptions, though considered a Gentleman's Agreement are to be followed as Good Amateur Practice. Ensure proper usage of each frequency and band before operating.</p> <p>Name:</p> <p>Call:</p>
<p>US Amateur Radio Bite Sized Band Plans FCC Effective Date: 03/05/12</p> <h2>VHF</h2> <p>Band limits are to be followed according to the operator's license class privileges. Operators must stay within the band edges providing enough room for transmitting mode bandwidth. 1600 Watts PEP output is allowed to all non-Beacons unless otherwise noted. Please stay within FCC section 97 guidelines. The lower Band Plan descriptions, though considered a Gentleman's Agreement are to be followed as Good Amateur Practice. Ensure proper usage of each frequency and band before operating.</p> <p>6 Meters 50.00-54.00 50.00-50.10 CW Only • 50.10-54.00 All Modes Technician • General • Advanced • Extra</p> <p>50.00-50.10 CW Beacons 50.060-50.080 Beacon Subband 50.10-50.30 SSB, CW 50.10-50.125 DX Window 50.125 SSB National Calling Freq. 50.30-50.60 All Modes 50.60-50.80 Nonvoice Communications 50.62 Digital (Packet) Calling 50.80-51.00 Radio Remote Cont. (20Watt Chan.) 51.00-51.10 Pacific DX Window 51.12-51.48 Repeater Inputs (19 Channels) 51.12-51.18 Digital Repeater Inputs 51.62-51.68 Repeater Outputs (19 Channels) 51.62-51.68 Digital Repeater Outputs 52.00-52.48 Repeater Inputs (23 Channels) 52.02-52.04 FM Simplex 52.20 Test Pair (Input) 52.50-52.98 Repeater Output (23 Channels) 52.92 FM Simplex / Natl. Calling Freq. 52.94 Secondary FM Simplex 52.94 Test Pair (Output) 53.00-53.48 Repeater Inputs (19 Channels) 53.00 Remote Base FM Simplex 53.02 Simplex 53.10-53.20 Radio Remote Control 53.30-53.40 Repeater Outputs (19 Channels) 53.50-53.60 Radio Remote Control 53.70-53.80 Simplex 53.82-53.90 Simplex</p>	<p>2 Meters 144.00-148.00 144.00-144.10 CW Only • 144.10-148.00 All Modes Technician • General • Advanced • Extra</p> <p>144.00-144.05 EME (CW) 144.05-144.10 General CW / Weak Signals 144.200 SSB National Calling Freq. 144.200-144.225 General SSB Operation 144.275-144.300 Propagation Beacons 144.30-144.50 New OSCAR Subband 144.50-144.60 Linear Translator Inputs 144.60-144.80 FM Repeater Inputs 144.90-145.10 Weak Signal / FM Simplex 145.01,02,03,07 Packet 145.10-145.20 Linear Translator Outputs 145.20-145.50 FM Repeater Outputs 145.50-145.80 Miscellaneous / Experimental 145.80-146.00 OSCAR Subband 146.01-146.37 Repeater Inputs 146.40-146.58 Simplex 146.52 FM Natl. Simplex Calling Freq. 146.61-146.97 Repeater Outputs 147.00-147.39 Repeater Outputs 147.42-147.57 Simplex 147.60-147.99 Repeater Inputs</p> <p>1.25 Meters 222.00-225.00 (219.00-220.00) Fixed Digital Message Forwarding 222.00-222.15 Weak-Signal Modes 222.02-222.05 EME 222.05-222.06 Propagation Beacons 222.10 SSB CW Natl. Calling Freq. 222.10-222.15 Weak-Signal CW & SSB 222.15-222.25 Local Coordinator's Option: Weak Signal, ACSS, Repeater Inputs, Control 222.25-223.38 FM Repeater Inputs Only 223.20-223.32 FM Simplex 223.30 FM Natl. Calling Freq. 223.32-223.64 Digital Packet 223.64-223.70 Links, Control 223.71-223.85 Local Coordinator's Option: FM Simplex, Packet, Repeater Outputs 223.85-224.98 Repeater Outputs Only</p> <p>PLANS ! Notice - 25 w PEP ©2012 Mike Maynard K4ICY • k4icy@arrl.net Free PDF - Visit k4icy.com</p>	<p>US Amateur Radio Bite Sized Band Plans FCC Effective Date: 03/05/12</p> <h2>UHF</h2> <p>70 Centimeters 420.00-450.00 Technician • General • Advanced • Extra 420.00-426.00 ATV Repeater, Simplex & Experimental with 421.25 MHz video carrier control links 426.00-432.00 ATV Simplex with 421.25 MHz video carrier control links 432.00-432.07 EME (Earth-Moon-Earth) 432.07-432.10 Weak-Signal CW 432.10-432.32 SSB National Calling Frequency 432.32-432.40 Mixed-Mode / Weak-Signal Work 432.30-432.40 Propagation Beacons 432.40-433.00 Mixed-Mode / Weak-Signal Work 433.00-435.00 Auxiliary / Repeater Links 435.00-438.00 Satellite Only (Internationally) 438.00-444.00 ATV Repeater Input with 438.25 MHz video carrier freq. & repeater links 442.00-445.00 Repeater Inputs / Outputs (Local Option) 445.00-447.00 Local Option: Shared by Auxiliary, Control Links, Repeaters & Simplex 446.00 FM National Simplex Frequency 447.00-450.00 Repeater Inputs / Outputs (Local Option)</p> <p>33 Centimeters 902.00-928.00 Technician • General • Advanced • Extra 902.000 Narrow-Bandwidth Weak-Signal 902.0-902.8 SSV, FAX, ACSS, Experimental 902.1 Weak-Signal Calling Frequency 902.8-903.0 Reserved for EME, CW Expansion 903.1 Allowable Calling Frequency 903.0-906.0 Digital Communications 906-909 FM Repeater Inputs 909-915 ATV 915-918 Digital Communications 918-921 FM Repeater Outputs 921-927 ATV 927-928 FM Simplex and Links</p> <p>Additional Bands All Classes Except Novice 2300-2510 MHz 2390-2450 MHz 3300-3600 MHz 6650-5925 MHz 10.0-10.5 GHz 24.0-24.25 GHz 47.0-47.2 GHz 76.0-81.0 GHz 122.25-123.0 GHz 134-141 GHz 241-250 GHz 275+ GHz</p> <p>PLANS ! ALL FREQUENCIES ABOVE 420 MHz - GEOGRAPHIC RESTRICTIONS APPLY !</p>	<p>23 Centimeters 1240.0-1300.0 1240-1245 ATV #1 1245-1248 Narrow-Bandwidth FM Point-to-Point Links and Digital Duplex with 1250-1260. 1248-1258 Digital Communications 1252-1258 ATV #2 1258-1260 Narrow-Bandwidth FM Point-to-Point Links Digital, Duplexed with 1245-1252 1260-1270 Satellite Opticals, Reference WARC 79 1260-1270 Wide-Bandwidth Experimental, Simplex ATV 1270-1276 Repeater Inputs, FM and Linear, Paired with 1280-1288, 288 Paired Every 25 MHz, e.g. 1270/1285, 050, etc. 1271-1283 Non-Coordinated Test Pair 1276-1282 ATV #2 1282-1288 Repeater Outputs, Paired with 1270-1276 1288-1294 Wide-Bandwidth Experimental, Simplex ATV 1294-1295 Narrow-Bandwidth FM Simplex Stations 1294.5 FM National Simplex Calling Frequency 1295-1297 Narrow Bandwidth Weak-Signal (no FM) 1295.0-1295.8 SSV, FAX, ACSS, Experimental 1295.8-1296.0 Reserved for EME, CW Expansion 1296.0-1296.05 EME-Exclusive 1296.01-1296.08 CW Beacons 1296.1 CW SSB National Calling Frequency 1296.4-1296.6 Crossband Linear Translator Input 1296.6-1296.8 Crossband Linear Translator Output 1296.8-1297.0 Experimental Beacons (Exclusive) 1297-1300 Digital Communications</p> <p>PLANS ! Notice for PEP Only - 1270-1295 MHz</p>

Cut

Cut

Cut or Fold